







DAEX25X4-4 Bullfrog Vented Disc Spider 25 mm x 4 Exciter 320 mm Cable and Connectors 40W 8 Ohm



PARAMETERS	
Impedance	8 ohms
Re	7.3 ohms
Le	0.29 mH
Fs	285 Hz
Qms	N/A
Qes	N/A
Qts	N/A
Mms	N/A
Cms	N/A
Sd	N/A
Vd	N/A
BL	N/A
Vas	N/A
Xmax	N/A
VC Diameter	4 x 25 mm
SPL	N/A
RMS Power Handling	40 watts
Usable Frequency Range (Hz)	N/A

- ### FEATURES
- Pre-applied 3M™ VHB™ adhesive for quick, secure installation
 - Four 24mm voice coils improves power handling to 40 watts RMS
 - Rare-earth neodymium motor and a proprietary voice coils
 - Easy 8 ohm load, can be powered by most amplifiers

- ### APPLICATIONS
- Invisible home theater and multi-room audio
 - Electronic gaming machines
 - Advertising signage
 - Point-of-purchase displays
 - Multimedia exhibits
 - Commercial distributed audio
 - Kiosks
 - Automotive audio
 - Bathroom tubs and showers



OmniMic

1/3rd octave smoothing - measurement taken with transducer adhered off-center on a 12" x 12" x 1/2" foam core board in an infinite baffle setup.

Note: This information is for comparison purposes only, the actual frequency response will depend on many factors of which the diaphragm being the greatest contributor.