


CH170Z



Dual cone

Treated cellulose fiber diaphragm
Rubber surround


GENERAL SPECIFICATIONS

Program power	150 W
Rated impedance	4 Ω
Nominal diameter	6,5"- 165 mm
Sensitivity (1W/1m)	90 dB
Voice coil diameter	25 mm
Frequency range	-

TECHNICAL SPECIFICATIONS

Power handling capacity	60 W
Gap height	5 mm
N. of mounting holes	4 ø 5 / ø 157
Front mount baffle cutout ø	142 mm
Re	3,50 Ω
Fs	93 Hz
Qms	4,25
Qes	2,63
Qts	1,62
Mms	9,51 g
Cms	0,30 mm/N
D	130 mm
Vas	7,47 dm³
B · l	2,73 Wb/m
Xmax	1,25 mm
η ₀	-
Le	-
Net weight	0,97 Kg
Recommended loading	-
Volume / Tuning Frequency	-

CZ140



2 Coaxial way

Treated cellulose fiber diaphragm
Neodymium tweeter

GENERAL SPECIFICATIONS

Program power	90 W
Rated impedance	4 Ω
Nominal diameter	6"X4"- 150X96 mm
Sensitivity (1W/1m)	91 dB
Voice coil diameter	25 mm
Frequency range	-

TECHNICAL SPECIFICATIONS

Power handling capacity	40 W
Gap height	4 mm
N. of mounting holes	4 ø 5 / ø 73 x 123
Front mount baffle cutout ø	ell. 144x87 mm
Re	3,50 Ω
Fs	159 Hz
Qms	6,80
Qes	1,73
Qts	1,38
Mms	3,63 g
Cms	0,28 mm/N
D	99 mm
Vas	2,29 dm³
B · l	2,71 Wb/m
Xmax	1,10 mm
η ₀	-
Le	-
Net weight	0,48 Kg
Recommended loading	-
Volume / Tuning Frequency	-