

## ARQIS106

### CABINET LOUDSPEAKERS

#### *Architectural Loudspeaker Cabinet*



### PRODUCT OVERVIEW

ARQIS106 is a 2-way wooden loudspeaker cabinet with a compact format, stylish aesthetics, excellent sound quality and long term reliability, featuring 120 WRMS @ 8 ohm, 6,5" woofer and 1" HF Compression Driver. Its smart wall bracket (included), allows for pan & tilt adjustment, employing a single screw for fastening. It has been specifically designed to fulfil permanent installation requirements where a perfect balance between sound performance and architectural/interior's design matching is a must.

### KEY FEATURES


- Full range, 2-way architectural loudspeaker
- 120 WRMS @ 8 ohm
- 6.5" low frequency woofer
- 1" high frequency compression driver (rotatable)
- Double INPUT/STACK connector, Euroblock type, with security attachment screws to avoid accidental disconnection
- Wall bracket included, allowing for pan & tilt adjustment, employing a single screw for fastening
- Metal safety sling included, to avoid drops in case of accidental detachment from the wall surface
- Available in black or white finish

### APPLICATIONS

- Shopping malls
- Sports centres
- Theatres / auditoriums
- Conference rooms
- A/V presentations
- Corporate rooms
- Perimeter reinforcement in clubs
- Cafés
- Restaurants
- Theme parks


POLAR DIAGRAMS

HORIZONTAL




Curve	Freq	BW	Q	DI
—	125.00	360	1.0	0.0
- - -	250.00	360	1.0	0.0
⋯	500.00	200	1.8	2.6
—	1.00K	131	2.7	4.4
- - -	2.00K	113	3.2	5.0
- - -	4.00K	87	4.1	6.2
—	8.00K	40	9.0	9.5

VERTICAL



Curve	Freq	BW	Q	DI
—	125.00	360	1.0	0.0
- - -	250.00	360	1.0	0.0
⋯	500.00	204	1.8	2.5
—	1.00K	142	2.5	4.0
- - -	2.00K	87	4.1	6.2
- - -	4.00K	76	4.7	6.7
—	8.00K	55	6.6	8.2

## FREQUENCY RESPONSE



## TECHNICAL DATA

<b>Ways</b>	2
<b>Impedance</b>	8Ω
<b>RMS power</b>	120 WRMS
<b>Program power</b>	240 WRMS
<b>Sensitivity</b>	92dB
<b>Sound pressure</b>	116dB
<b>Frequency response (±3dB)</b>	75Hz÷19kHz
<b>Cross-over frequency</b>	3.2kHz
<b>Dispersion (HxV)</b>	90°x60°
<b>Driver LF/MF</b>	6.5"
<b>Driver HF</b>	Compression driver 1"
<b>Connection</b>	Euroblock 2 ways
<b>Dimensions (WxHxD)</b>	216x350x240mm
<b>Weight</b>	7.4kg
<b>Color</b>	Black (RAL 9005) / White (RAL 9016)