


ARQIS110

CABINET LOUDSPEAKERS

Architectural Loudspeaker Cabinet



PRODUCT OVERVIEW

ECLER ARQIS 110 is a wooden loudspeaker cabinet with a compact format, stylish aesthetics, excellent sound quality and long term reliability, featuring 220 WRMS @ 8 ohm, 10" woofer and 1" HF Compression Driver. 35 mm mount socket and 8 x M8 rigging points, allowing for horizontal or vertical mounting options (90°x50° dispersion pattern). It has been specifically designed to fulfil permanent installation requirements where a perfect balance between sound performance and architectural/interior's design matching is a must.

KEY FEATURES

- Full range, 2-way architectural loudspeaker
- 220 WRMS @ 8 ohm
- 1 x 10" low frequency woofer
- 1" high frequency compression driver (rotatable)
- Double INPUT/STACK connector, Euroblock + Speakon® type, with security attachment screws to avoid accidental disconnection
- 35 mm mount socket, compatible with SR12 wall bracket (not included) & TRIPO1 floor stand (not included)
- U-bracket wall-mount accessory compatible (not included)
- 8 x M8 cabinet flying points.
- Metal safety sling included, to avoid drops in case of accidental detachment from the wall surface
- Available in black or white finish

APPLICATIONS


- Shopping malls
- Sports centres
- Theatres / auditoriums
- Conference rooms
- A/V presentations
- Corporate rooms
- Perimeter reinforcement in clubs
- Cafés
- Restaurants
- Theme parks

ACCESSORIES AND COMPATIBLE PRODUCTS

- ARQ110UB (U-bracket wall-mount)
- SR12 (Wall-mount bracket)
- TRIPO1 (Loudspeaker floor stand)




TRIPO1



ARQ110UB


POLAR DIAGRAMS

HORIZONTAL




Curve	Freq	BW	Q	DI
—	125.00	360	1.0	0.0
- - -	250.00	360	1.0	0.0
⋯	500.00	149	2.4	3.8
—	1.00K	120	3.0	4.8
- - -	2.00K	95	3.8	5.8
⋯	4.00K	73	4.9	6.9
—	8.00K	76	4.7	6.7

VERTICAL



Curve	Freq	BW	Q	DI
—	125.00	360	1.0	0.0
- - -	250.00	360	1.0	0.0
⋯	500.00	153	2.4	3.7
—	1.00K	113	3.2	5.0
- - -	2.00K	98	3.7	5.6
⋯	4.00K	76	4.7	6.7
—	8.00K	55	6.6	8.2

FREQUENCY RESPONSE



TECHNICAL DATA

Ways	2
Impedance	8Ω
RMS power	220 WRMS
Program power	440 WRMS
Sensitivity	95dB
Sound pressure	118dB
Frequency response (±3dB)	60Hz±18kHz
Cross-over frequency	3.5kHz
Dispersion (HxV)	90°x50°
Driver LF/MF	10"
Driver HF	Compression driver 1"
Connection	Euroblock 2 ways + Speakon® 4 ways
Dimensions (WxHxD)	359x495x310mm
Weight	14.8kg
Color	Black (RAL 9005) / White (RAL 9016)